



StructuredGround™ CTAPF4-12-C Comp. Tap, Copper, Copper, PK100

CTAPF4-12-C

The CTAPF4-12-C Compression Connector Tap provides high-strength and premium electrical properties. It is suitable for use with stranded copper code conductors and is for tapping into unbroken continuous main, splicing and pig tailing. The wide wire range-taking capability minimizes inventory requirements. UL listed per UL486 for use up to 600V and temperature rated to 90°C when crimped with Panduit and specified competitor crimping tools and dies.

Specifications

Sub Brand	StructuredGround™
Maximum Tap Size (AWG STR)	6
Minimum Tap Size (AWG STR)	12
Maximum Run Size (AWG STR)	4
Minimum Run Size (AWG STR)	6
Overall Length (In.)	1.25
Overall Length (mm)	31.8
Color	Brown
Overall Thickness (In.)	0.07
Overall Thickness (mm)	1.78
Overall Width (In.)	0.4
Overall Width (mm)	10.16
Panduit Die Index Number	P33
Wire Strip Length (In.)	1.3125
Wire Strip Length (mm)	33.3
Inside Diameter (In.)	0.4
Inside Diameter (mm)	10.2
For Use With	AWG wire only
Standards Met	UL listed and CSA certified to 600 V
Application	Utility/Ground Grid
Product Type	Compression Tap
Material	Copper
Surface Treatment	Bare

Packaging Detail

UPC	07498359973
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0528
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000