

YAV8CL1, Cu Compression, 1-Hole, 1/4" Stud, Standard Barrel, 8 Flex

By Burndy Catalog # YAV8CL1

Copper Compression Lug, Ring Tongue, 1 Hole w/ Inspection Hole, AN-8 Flex, 1/4" Stud, Short Barrel, Tin Plated.

Features

- Manufactured from seamless pure electrolytic copper tubing to provide maximum conductivity, low resistance and excellent ductility for crimping
- Seamless tubular crimp barrel design No seams to split resulting in a very high quality electrical connection, also can be used on solid conductor
- Double thick tongue structurally a very strong terminal tongue
- Produced from tubular copper, extra copper material assures the compression connector will operate cooler than the conductors it connects
- Internally bevelled barrel for easy cable entry, especially for flexible conductors
- Inspection hole provides easy visual check for proper conductor insertion
- Electro-tin plated for a long lasting durable corrosion resistance

Application

For Use On Type AN Aircraft Cable, Extra Flexible Conductors And Commercial (Code) Conductors, Industrials, Hospitals, Electric Utilities, Marine, Computers, And Other Equipment Subject To Vibration Or Requiring Dependable Electrical Performance

General

Application - For Use On

Catalog Number Connector Type Die Index EU RoHS Indicator Feature - Barrel Style Feature - Barrel Type Material Material Composition

Military Specification Physical Attribute - Number of Holes

Copper Commercial (Code) Cable, Type AN Aircraft Cable, Extra Flexible Conductors YAV8CL1 Ring Terminal 38 Yes Chamfered Standard Copper • DLP Copper • Tin Plating AS20659 1



Physical Attribute - Tongue	Ring
Туре	
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	HYLUG
Trade Name	HYLUG™
Туре	Ring Tongue
UPC	781810025079

Dimensions

Dimension - B Length inch	0.405 in
Dimension - Bolt Size fraction	1/4
Dimension - Length Overall	1.22 in
inch	
Dimension - N inch	0.25 in
Dimension - Outside Diameter	0.27 in
inch	
Dimension - Pad Width inch	0.46 in
Dimension - Stud Size inch	1/4

Conductor Related

Conductor - Copper Str	AN-8	
Aircraft Size		
Conductor - Copper Str Size	8 AWG	
Conductor - Copper Str Size	8 AWG	
Range		
Conductor Size	8 AWG	
Conductor Type	• CU C Solid-Size	
	 CU C Str-Size 	

Certifications And Compliance

Buy American Compliant Yes Certification - CSA Approved Yes Certification - ETL No Certification - UL Recognized No Certification - cULus No Industry Standard(s) • UL467 Military Specified (Mil-Spec) Standards - Industry Standards UL486 Met Standards - RoHS Compliance CM Status UL Listed Yes

1	1 1	
LOg	IST	ICS

Carton Quantity	200
Minimum Pack Quantity	200
Pallet Quantity	99999

Product Assets

3D Models - YAV8CL1_MODEL-STEP



A Hubbell brand

3D Models - YAV8CL1_MODEL-PDF 3D Models - YAV8CL1_MODEL-IGES Catalogs - BURNDY Master Catalog - Section B - Small Compression Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_YAV10L36BOX_LineArt Sales Drawings - 50094161_E Specifications - YAV8CL1

> ©2024 Hubbell Incorporated. All rights reserved BRDY-YAV8CL1-SPEC-EN | REV 10/2024