Specifications







Eaton DRS-1215

14-Outlet Economy Network Server Surge Protector, 15 ft. (4.57 m) Cord, 3000 Joules, 1U Rack-Mount

General specifications	
PRODUCT NAME	Eaton Tripp Lite series surge protector
CATALOG NUMBER	DRS-1215
UPC	037332100245
PRODUCT LENGTH/DEPTH	4 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	17.5 in
PRODUCT WEIGHT	4.96 lb
WARRANTY	Limited lifetime
COMPLIANCES	RoHS
CERTIFICATIONS	CSA Std. C22.2 UL Listed
GLOBAL CATALOG	DRS-1215
PRODUCT TYPE	Surge protector

Powering Business Worldwide

Product specifications

SAFE THERMAL FUSING	Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences
STORAGE HUMIDITY RANGE	5% to 95% RH
SURGE STYLE	RM - RACKMOUNT
SWITCHES	Power switch controls power to all outlets
VOLTAGE COMPATIBILITY (VAC)	120
CIRCUIT BREAKER	15
FREQUENCY RATING	50/60 Hz
DIAGNOSTIC LED DETAILS	Green - Protection Present
EMI / RFI FILTERING	40-80 dB
FORM FACTOR	1U rackmount, 0U vertical rackmount, wallmount and under-counter mounting supported
IMMUNITY	Conforms to IEE 587 / ANSI C62.41
LOCKING SWITCH COVER	Transparent locking switch cover prevents accidental shutoff
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
PROTECTION MODES	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
RECEPTACLE COLOR	BLACK
RECOMMENDED ELECTRICAL SERVICE	120V (110-125V)
STORAGE TEMPERATURE RANGE	14° to 122°F (-10° to 50°C)
UL1449 LET THROUGH RATING	330V
CORD LENGTH	15 Foot
POWER CORD COLOR	Black
HOUSING COLOR	Black
OUTLET SPACING	Distance between front outlets = 38.9mm; Distance between rear outlets = 38.9mm
OUTLETS MEASUREMENT (CENTER TO CENTER)	Distance between front outlets = 38.9mm; Distance between rear

Resources

BROCHURES	Surge Protectors and Power Strips Brochure Surge Protector and Power Strip Specification Brochure (English)
DRAWINGS	Rackmount Surge Suppressors and Power Strips Visio Stencil Preview Rackmount Surge Suppressors and Power Strips Visio Stencil
MANUALS AND USER GUIDES	Owner's Manual for Rackmount Power Strips and Isobar Rackmount Surge Suppressors

	outlets = 38.9mm
MATERIAL	Metal
MOUNTING DETAILS	Includes flanges
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R
PACKAGE CONTENTS	DRS-1215 Surge Suppressor Instruction manual Warranty information
INPUT NOMINAL VOLTAGE	120 VAC 120V AC
PRODUCT FEATURES	Diagnostic LED(s) Metal Case Mounting Accessory Included UL Certified
PRODUCT HIGHLIGHTS	3000 joule rating Adjustable rackmount hardware Lifetime limited warranty (Worldwide) 14 outlets / 15-ft. (4.57 m) cord
PLUG COLOR	White
AC SUPPRESSION JOULE RATING	3000
AC SUPPRESSION RESPONSE TIME	< 1 ns
MAXIMUM SURGE AMPS	120000
OPERATING HUMIDITY RANGE	10% to 90% RH
INCLUDED MOUNTING ACCESSORY	Included mounting flanges are pre-installed for 1U rackmount installation and can be re-configured to support a variety of mounting options
TOTAL OUTLETS	14

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.