

HSC200FR, PVC Clear Heat Shrink Tubing, 800-1000 Code, 500-750 Flex, 600 V, Fire Retardant.

By Burndy Catalog # HSC200FR





- Flame Retardant
- Flexible Polyvinylchloride
- 2:1 Shrink Ratio
- 600 Volts

Application

For Terminations And Splices

General

Catalog Number HSC200FR Color Clear

Connector Type CLEAR TUBES

EU RoHS Indicator Yes

MaterialPolyvinyl chlorideSub BrandVISISHRINKTrade NameVISI-SHRINK™

Type HSC-FR, Thin Wall, Flexible,

Fire Retardant

UPC 781810266236

Conductor Related



Conductor Size 800kcmil - 1000kcmil

Certifications And Compliance

Buy American Compliant Yes
Certification - CSA Approved Yes
Certification - ETL No
Standards - RoHS Compliance CM

Status

UL Listed No

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog

Literature - Polyolefin Thin Wall Heat Shrink Cross Reference

Guide

Product Cross Section Image(s) - BUR_HSC100FR_LineArt

Sales Drawings - 50015598 Specifications - HSC200FR

