

FEATURED



Aqua LC, Multimode Duplex Fiber Adapter

FADSLCZAQ-L

The LC duplex adapter connects two LC connector pairs in one module space and features an aqua, multimode fiber adapter and has zirconia split sleeves. This part (ending in -L) is a pack of 50 adapters.

Specifications

Sub Brand	Opticom®
Body Style	Duplex
Fiber Type	OM4
Material	Zirconia Ceramic
Overall Length (In.)	1.73
Overall Length (mm)	43.9
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	0
Minimum Operating Temperature (°F)	32
Maximum Installation Temperature (°C)	60
Maximum Installation Temperature (°F)	140
Minimum Installation Temperature (°C)	0
Minimum Installation Temperature (°F)	32
Resistance Properties	Flame-Resistant
Standards Met	RoHS compliant
Product Type	LC Adapter Module
Application	Mini-Com Modules, Patch Panels, Faceplates, Surface Mount Boxes
Color	Aqua
Connection Type	LC Duplex

Packaging Detail

UPC	07498337642
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0802
Std. Ctn. Qty.	100
Std. Ctn. Volume (cf)	0.1604