

Four-Pair Termination Tool For MT-Series Keystone Jacks

KEY FEATURES




- Simultaneous termination of eight twisted-pair conductors along with conductor excess trimming
- Comfortable plastic handle grips
- Lightweight and compact, fits most tool pouches' compartments
- Replaceable die
- Tool and die are bright-colored – easy to find when left behind
- When not used, the tool may be stowed by using the integrated lock



Signamax 4-pair termination tool is designed to work with the following Signamax MT-series keystone jacks:

KJ458MT-C6AC-XX
KJS458MT-C6AC
KJ458MT-C6C-XX
KJS458MT-C6C
KJ458MT-C5E-XX
KJS458MT-C5E
KJ126MT-C3U-XX

Simultaneous termination of all eight twisted-pair cable conductors along with trimming of conductor excess allows to save installation time, provides reliable termination means in confined areas, while ensuring precise and consistent termination of all pairs due to the calibrated die drive mechanism.



FOUR-PAIR TERMINATION TOOL FOR MT-SERIES KEYSTONE JACKS

PART NUMBER	DESCRIPTION
KJMT-8600	4-Pair Termination Tool For All MT Series Keystone Jacks

SPECIFICATIONS

JACK TYPE

8p8c (8-position, 8-contact) "RJ45" type
Signamax MT-series high-density keystone jacks only

CONDUCTOR TYPE

Insulated copper

WIRE GAUGE

22-24 AWG (0.644–0.511 mm)

CONSTRUCTION

Framework: steel alloy
Handle casing: high-impact thermoplastic
Die: high-impact thermoplastic, tool steel

CONTACT TYPE

110-style IDC

DIMENSIONS

Stowed: D 165 mm H 80 mm W 30 mm
D 6.5 in H 3.2 in W 1.2 in
Operational: D 165 mm H 150 mm W 30 mm
D 6.5 in H 5.9 in W 1.2 in

ENVIRONMENTAL CONDITIONS

Storage: -40 °C – +70 °C (-40 °F – +158 °F)
Operation: -10 °C – +60 °C (+14 °F – +140 °F)
RH (operation): max non-condensing 93 %