



Pan-Lug™ LCDX2-38D-E Compression Connectors - Lugs

LCDX2-38D-E

Two-hole, flex lug, #2 AWG wire, 3/8 stud hole, 1 hole spacing.

Specifications

Product Type	Compression Lug
Base Material	Copper
Class G Copper Flex Conductor Size (AWG)	2
Class H Copper Flex Conductor Size (AWG)	2
Class I Copper Flex Conductor Size (AWG)	2
Class K Copper Flex Conductor Size (AWG)	2
Class M Copper Flex Conductor Size (AWG)	2
Copper Code Conductor Size (AWG)	2
DLO Copper Flex Conductor Size (AWG)	2
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	3/8
Stud Hole Size (mm)	9.5
Stud Hole Spacing (In.)	1
Stud Hole Spacing (mm)	25.4
Barrel Type	Standard Barrel Length with Inspection Window
Barrel Length (In.)	0.59
Barrel Length (mm)	15
Tongue Type	Standard
Tongue Width (In.)	0.7
Tongue Width (mm)	17.8
Tongue Thickness (In.)	0.11
Tongue Thickness (mm)	2.8
Overall Length (In.)	2.7
Overall Length (mm)	68.6
Finish/Coating	Tin-Plated
UL Temperature Rating (°C)	90
Maximum Voltage (kV)	35

Specifications (continued)

Color Code	Brown
Panduit Die Index Number	P33
Burndy Die Index Number	10
Wire Strip Length (mm)	17
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window, beveled wire entry.

Packaging Detail

UPC	07498342372
Std. Pkg. Qty.	20
Std. Pkg. Volume (cf)	0.0328
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000