



## StrongHold™ JP131DW-L20 J-Hook, 0.25", Blk, PA 6.6/Metal, Hammer-on, 1.31", PK50

JP131DW-L20

Panduit JP131DW-L20 J-Hook with Drop Wire and Rod Clip has a patented design, featuring complete horizontal and vertical 1" bend radius control, which prevents pinch points and degradation of cable performance. They are suitable for use in air handling spaces and are UL listed. For use with #12 wire, threaded rod up to 3/8" (9.5mm) in diameter or 1/8" - 3/8" (3.2mm-9.5mm), 1.31" (33.3mm) max. bundle capacity. Made of Nylon 6.6, are black in color, and come in packages of 50.

### Specifications

|                                |                                                                     |
|--------------------------------|---------------------------------------------------------------------|
| Application                    | Route High Performance Communication Cabling in Air Handling Spaces |
| Product Type                   | Cable Support                                                       |
| Category 5e Cable Capacity     | 29                                                                  |
| Category 6 Cable Capacity      | 25                                                                  |
| Category 6A Cable Capacity     | 15                                                                  |
| Color                          | Black                                                               |
| For Use With                   | #12 Wire and Threaded Rod                                           |
| Includes                       | Clip                                                                |
| Material                       | Nylon 6.6/Metal                                                     |
| Maximum Flange Thickness (In.) | 0.25                                                                |
| Maximum Flange Thickness (mm)  | 6.4                                                                 |
| Maximum J-Hook Bundle Capacity | 33.34                                                               |
| Mount Method                   | Hammer-On                                                           |
| Overall Height (In.)           | 5                                                                   |
| Overall Height (mm)            | 126.4                                                               |
| Overall Length (In.)           | 2.5                                                                 |
| Overall Length (mm)            | 62.8                                                                |
| Overall Width (In.)            | 2.5                                                                 |
| Overall Width (mm)             | 62.8                                                                |
| Standards Met                  | UL, cULus Listed, RoHS Compliant                                    |
| Sub Brand                      | StrongHold™                                                         |
| Static Load Capacity (kg)      | 4.5                                                                 |
| Static Load Capacity (lb)      | 10                                                                  |
| Support Type                   | J-PRO Pre-Assembled J-Hook System                                   |
| Part Features                  | Bend Radius Control, Smooth Pulling Surface                         |

**Packaging Detail**

|                       |             |
|-----------------------|-------------|
| UPC                   | 07498344040 |
| Std. Pkg. Qty.        | 50          |
| Std. Pkg. Volume (cf) | 0.7051      |
| Std. Ctn. Qty.        | 0           |
| Std. Ctn. Volume (cf) | 0.0000      |