



Dry-Shrink™ HSTT25-C2 Heat Shrink

HSTT25-C2

Thin wall heat shrink, .25" (6.4mm) diameter, red cross-linked polyolefin, 100 ft. (30.5m) per reel.

Specifications

Product Type	Heat Shrink Tubing
Adhesive Lined	No
Color	Red
Material	Cross-Linked Polyolefin
Maximum Operating Temperature (°C)	135
Maximum Operating Temperature (°F)	275
Minimum Operating Temperature (°C)	-55
Minimum Operating Temperature (°F)	-67
Nominal Diameter (In.)	0.25
Nominal Diameter (mm)	6.4
Nominal Recovered Wall Thickness (In.)	0.025
Nominal Recovered Wall Thickness (mm)	0.6
Sub Brand	Dry-Shrink™
Overall Length (In.)	1200
Overall Length (ft.)	100
Overall Length (m)	30.5
Overall Length (mm)	30480
Resistance Properties	Flame-Retardant
Standards Met	UL Recognized, CSA Approved, MIL SPEC
Shrink Ratio	2:1
Shrink Temperature (°C)	90
Shrink Temperature (°F)	194
Maximum Recovered Inside Diameter (In.)	0.125
Maximum Recovered Inside Diameter (mm)	3.2
Minimum Expanded Inside Diameter (In.)	0.25
Minimum Expanded Inside Diameter (mm)	6.4
Application	For Dry Locations

Packaging Detail

UPC	07498374711
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.4230
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	4.2297