

Specifications

Eaton PDU2430



Eaton Tripp Lite series basic PDU, 1PH, 1U, NEMA L5-30P input, 15 ft cord, 2.9kW, 24A, 120V, 24 Outlets (24) 5-15R



General specifications

PRODUCT NAME	Eaton Tripp Lite series basic PDU
CATALOG NUMBER	PDU2430
UPC	037332117281
PRODUCT LENGTH/DEPTH	4.5 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	17.25 in
PRODUCT WEIGHT	7.4 lb
COMPLIANCES	RoHS TAA Compliant
CERTIFICATIONS	UL 1778 CSA Std. C22.2

Product specifications

FORM FACTOR	1U
PHASE	Single-phase
AMPERAGE RATING	24A
INPUT CONNECTION	NEMA L5-30P
CORD LENGTH	15 ft
FREQUENCY RATING	50/60 Hz
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)

Resources

BROCHURES

[120V Power Distribution Unit \(PDU\) Models and Specifications List \(English\)](#)

[230V Power Distribution Unit \(PDU\) Brochure \(English\)](#)

[120V Power Distribution Unit \(PDU\) Brochure \(English\)](#)

[Integrated Solutions Brochure \(English\)](#)

[120V PDU Brochure Specifications \(Spanish\)](#)

[Rack Models and Specifications Brochure \(Spanish\)](#)

DRAWINGS

[Single Phase Power Distribution Units \(PDUs\) Visio Stencil](#)

[Single-Phase Power Distribution Units \(PDUs\) Stencil Preview](#)

MANUALS AND USER GUIDES

[Owner's Manual for PDU Rackmount Power Strips](#)

PRODUCT PAGE (WEB)

[PDU2430 Tripp Lite Model Page](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

