



## **G5 PDU**

**P30B06M**

This Panduit™ G5 Basic PDU features (24) C13 and (6) C19 outlets. It is a 32 amp, 230 V, single phase PDU with an IEC 60309 2P+E 6h 32A (IP44) input plug and a 10 foot (3m) power cord. The PDU is black.

### **Specifications**

Note	CE Compliant Only
Includes	Mounting Hardware
Product Type	PDU
Mount Orientation	Vertical
Sub Brand	G5
Rack PDU Type	Basic
Plug Type	IEC 60309 2P+E 6h 32A (IP44)
Number of Circuit Breakers	2
Input Voltage (V)	230
Input Amperage (A)	32
Phase	Single Phase
Frequency Compatibility (Hz)	50/60
Input Cord Length (ft.)	3
Input Cord Length (m)	10
Output Receptacles	(24)C13, (6)C19
Output Voltage (V)	230
Output Capacity (kW)	7.4
Front Panel Display	No
Network Monitoring Port	No
SNMP Compatibility	No
Network Compatibility	No
Network Card	No
Communications Interface	No
Daisy-Chainable / Cascadable	No
LED Indicators	No
Material	Metal
Finish/Coating	Powder-Coated
Color	Black
Overall Height (In.)	59
Overall Height (mm)	1490

**Specifications (continued)**

Overall Width (In.)	2
Overall Width (mm)	52
Overall Depth (In.)	2.1
Overall Depth (mm)	53
Number of Rack Units	34
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	10
Minimum Operating Temperature (°F)	50
Maximum Storage Temperature (°C)	60
Maximum Storage Temperature (°F)	140
Minimum Storage Temperature (°C)	-20
Minimum Storage Temperature (°F)	-4
Compliance Certifications	RETIE (Colombia)
Standards Met	CE, UKCA, ROHS, REACH, China ROHS
Product Warranty Period (Worldwide)	3 Years

**Packaging Detail**

UPC	61305626375
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	1.5741
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000